

# P20000



**PULSTAR MANUFACTURING COMPANY**  
**P20000**  
Phone: 402-693-2599 Fax: 402-693-2681

The 20,000 Series Pump Hoist consists of a 36 ft. self-supporting telescoping mast held by two 4" x 48" double acting cylinders. This design eliminates the need for guy cables. Maximum layback is 8 ft. The basic rig consists of 20,000 lb. capacity (6,720 lb. single line), 180 ft. of 9/16" Flex X rotation resistant cable, open swage socket with 7 ton hook, hydraulic outriggers with lock valves, line parting blocks with 11 ton swivel hook, and double gear pto with direct mount heavy duty gear pump. Maximum single line speed is 135 fpm.

## **Standard Features:**

- Self-contained and sealed oil bath **planetary drive**
- 30 gallon oil capacity
- In-line cable weights
- 2,000 Series Char Lynn hydraulic motors (for added efficiency)
- Outside left oriented control handles (increased cargo bay storage)
- 60" rear outrigger width
- **Failsafe hydraulic disc brakes**
- Failsafe over-center hydraulic holding valves
- Extra high grade urethane paint
- Tailout winch with 125 ft. of 3/8" cable
- **Tower Load Status Gauge**
- Mast cylinder holding valves

## **Optional Features:**

- Remote control
- Sandreel
- Power to the rear
- Hydraulic wire winders
- Heavy duty tailgate
- Heavy duty pipe racks
- Front outrigger
- Hydraulic oil cooler