

P29000



PULSTAR MANUFACTURING COMPANY
P29000
Phone: 402-693-2599 Fax: 402-693-2681

P29000 basic rig includes the **standard primary mainline** and EXHD rotation resistant highly compacted cable, traveling block, outrigger and mast cylinder lock valves, 40 ft mast height, 11,000 lb max single line pulling capacity, 190 fpm max single line winch speed

- Add tapered roller bearing eye and hook swivel
- Add Lebus split sleeve grooving
- Add remote control and pendant for mainline
- Add remote control and pendant for tailout winch
- **2-speed** main winch (380fpm)
- Add special operator side control
- Additional mast height (per foot)
- Cathead with hydraulic source
- Breakout with hydraulic source
- Dual front outriggers w/lock valves
- Hydraulic source for power tongs
- Power tongs handler jib boom (specify manual or hydraulic)
- Hydraulic oil cooler w/auto on/off function
- Rig complete lighting package
- Factory mount (petroleum base fluid)
- Factory mount (synthetic base fluid)
- Delivery charge per mile (includes permits)
- Startup technician charge
- Flatbed, headache rack, matboard holders, underbody toolboxes,
- Mast cylinder holding valves

HD rear bumper

- Special paint color package
- Utility pneumatics plumbed to rear w/outlet

(A3) P29000 sandline#1, less cable and hook, 4000 lb max single line pulling capacity, 400 fpm max single line winch speed

- Sandline#2
- Sandline#3
- Sandline#4