

P38000



PULSTAR MANUFACTURING COMPANY

P38000

Phone: 402-693-2599 Fax: 402-693-2681

(A1) P38000 basic rig includes the **standard primary mainline** and EXHD rotation resistant highly compacted cable, traveling block, outrigger and mast cylinder lock valves, 40 ft mast height, 12700 lb max single line pulling capacity, 150 fpm max single line winch speed

- Add tapered roller bearing eye and hook swivel
- Add Lebus split sleeve grooving
- Add remote control and pendant for mainline
- Add remote control and pendant for tailout winch
- Add heavy hoist package (45000 lb capacity)
- **2-speed** heavy hoist package (300 fpm max speed)
- Add special operator side control
- Additional mast height (per foot)
- Cathead with hydraulic source
- Breakout with hydraulic source
- Dual front outriggers w/lock valves
- Hydraulic source for power tongs
- Power tongs handler jib boom
- Hydraulic oil cooler w/auto on/off function
- Rig complete lighting package
- Factory mount (petroleum base fluid)
- Factory mount (synthetic base fluid)
- Delivery charge per mile (includes permits)
- Startup technician charge
- Flatbed, headache rack, matboard holders, underbody toolboxes,
- Mast cylinder holding valves

HD rear bumper

- Special paint color package
- Utility pneumatics plumbed to rear w/outlet

(A3) P38000 **sandline#1**, less cable and hook, 4000 lb max single line pulling capacity, 400 fpm max single line winch speed

- Sandline#2
- Sandline#3
- Sandline#4
- Sandline#5
- Sandline#6
- Add Lebus split sleeve grooving
- Add remote control and pendant
- Add special operator side control