

**Pulstar**™

Hand Built by People Who Care

A Division of Preferred Pump & Equipment, LP

**P38**

Pulls up to 38,000 lbs.



# PULSTAR P38 PULLS UP TO 38,000 LBS.

## STANDARD FEATURES & SPECIFICATIONS

### PULLING

- 38,000 lbs. hook load accomplished by primary mainline and 2-part and 3-part line blocks
- Roller bearing sheaves
- Inner stinger may be fully extended and locked mechanically
- Mast is self-supporting and does not require guy cables in most operating conditions (additional tower heights, if selected, have individual load ratings and restrictions)
- We provide highly compacted, high-performance wire rope and also provide a tapered roller bearing eye and hook swivel, Pulstar-engineered 2-part and 3-part line blocks with roller bearing sheaves, and documented certification

### MAST & MAIN FRAME

- Pulstar-engineered and fabricated
- Load tested and proven
- Documented certification

### DERRICK ASSEMBLY

- Pulstar-engineered rectangular tubing
- Alloy tubing incorporated into stinger
- (8) elevating and holding hydraulic cylinders incorporated into elevation and holdback
- Once in the layback position, we can maintain 302,000 lbs. of holdback automatically, making our derrick truly self-supporting
- Documented certification

### WIRE ROPE

- Highly compacted and rotation-resistant
- High-performance configuration for state-of-the-art durability
- Documented certification

### PRIMARY MAINLINE

- Pulstar-engineered winch drum and drives
- Planetary reduction
- Failsafe hydraulic disc brakes
- High performance wire rope
- Eye and hook swivel and high-performance wire rope
- Documented certification

### TAILOUT WINCH

- Pulstar-engineered drum and drives
- Planetary driven
- Hydraulic failsafe brake
- Lebus grooving sleeve
- 140 FPM bare spool line speed
- 8,500 lbs. bare spool pull
- High-performance wire rope and swivel hook
- Documented certification

### HYDRAULIC SYSTEM

- Pressure-compensated, load-sensing pump
- Independent stacker control valves
- Remotes provided where noted
- Hydraulic reservoir heater
- Hydraulic oil cooler with auto ON/OFF thermostat
- Auxiliary hydraulics can be provided to the rear of rig with pressure compensation to provide power to power tongs and/or spinners

# PULSTAR P38 PULLS UP TO 38,000 LBS.

## STANDARD FEATURES & SPECIFICATIONS (continued)

### ADDITIONAL SAFETY ITEMS

- Hydraulic bypass valve will not allow over-pulling
- Hydraulic valving automatically puts system into standby pressure when derrick is lowered
- Electronic E-Kill technology incorporated into rig/truck system
- (2) E-Kill electronic switches located at rear of rig
- Documented certification

### OPTIONS (at additional cost)

- Lebus split sleeve grooving on any winch
- Heavy hoist option (increases overall capacity to 45,000 lbs.)
- Electronic shift on the fly
- Proportional remote control (tethered) on any winch
- Wireless remote control on any winch
- Cathead(s) with rollers
- Basic breakout wrench and hardware
- Dual breakout system with cables and fairleads
- Hydraulic jib boom
- Additional mast height (40' standard; 50' max)
- Rig complete lighting package (LED)
- Auxiliary hydraulics to the rear (basic)
- Hydraulic source for power tongs (intricate)
- Electronic spudder - well rehab
- Dual front outriggers (behind cab) with lock valves
- Cummins deck engine package
- Utility pneumatics plumbed to rear with outlet(s)

### SANDLINE OPTIONS

1. Direct drive / 400 FPM / 4,000 lbs. bare spool pull / Will hold 900' of 5/8" max
2. Planetary drive / 300 FPM / 8,000 lbs. bare spool pull / Will hold 900' of 5/8" max
3. Direct drive / 400 FPM / 4,000 lbs. bare spool pull / Will hold 2,000' of 5/8" max
4. Planetary drive / 300 FPM / 8,000 lbs. bare spool pull / Will hold 2,000' of 5/8" max

### FLATBED & OPTIONS

- 18' minimum length
- Under-body toolboxes (steel skeleton frame, aluminum boxes)
- Above-body toolboxes / aluminum boxes with tray kits
- EXHD non-towing bumper
- Headache rack
- Banding rail package (Deck width increases to 102")

**It is highly recommended that you allow Pulstar to supply a class 7 or class 8 truck - single rear axle or tandem rear axles, heavy-duty front axle, diesel engine, heavy ON/OFF road specs. Pulstar is FET Exempt.**