

Pulstar™

Hand Built by People Who Care

A Division of Preferred Pump & Equipment, LP

P7

Pulls up to 7,000 lbs.



PULSTAR P7

PULLS UP TO 7,000 LBS.

STANDARD FEATURES & SPECIFICATIONS

PULLING

3,500 lbs. bare-spool pull (Single Line)
7,000 lbs. bare-spool (Double Line)

PROPULSION

Direct-mount PTO - transmission

HYDRAULICS

Direct-mount PTO, gear or vane pump, open system valving
25 GPM max @ 2,500 PSI hydraulics
Hydraulic valve failsafe bypass protection

MAIN WINCH

Self-contained, sealed oil bath gearcase, hydraulic disc brake
Low-speed approx. 75 FPM @ 2,500 PSI
High-speed approx 150 FPM @ 2,500 PSI
7/16" HP wire rope with 5T swivel hook
Inline weight

REMOTE CONTROL

Tethered remote control

RIG MAIN FRAME*

Pulstar-designed and engineered

MAIN DERRICK & EXTENSION STINGER*

37' standard height, 44' max. extension height
11' max. layback

CONTROL PANEL

Electronic and manual hydraulic controls
Gauges, identifiers, and load rating plate

LEVELING HYDRAULIC CYLINDERS / JACKS

(2) 24" stroke independently controlled / rear
Holding lock valves

MAST ELEVATING HYDRAULIC CYLINDERS

(2) 3.5" x 48" with holding lock valves

OVERALL DIMENSIONS

20' (L) x 6' (W)
Derrick Up Height (Mounted on Class 3 Carrier): 38'
Derrick Down Height (Mounted on Class 3 Carrier): 9', 6"

OPTIONS (adds to overall cost)

CARRIER

Minimum: Dodge RAM 4500 DRW or Ford F-450 DRW

SERVICE BODIES

9' - 11' solid or top opening / various configurations

FLATBEDS

9' - 11' steel/alum. construction / various configurations

REMOTE CONTROL

Remote control adjustable response
Wireless remote control

OPTIONS (continued)

AUXILIARY HYDRAULICS TO REAR

0 - 25 GPM @ 2,500 PSI auxiliary hydraulics

SANDLINE WINCH

Freefall or non-freefall style 2,000 lbs. (Bare drum)
"Sandline Ready" option available

CATHEAD

Multiple styles available (Requires auxiliary hydraulics to rear)

HYDRAULIC OIL COOLER

Auto ON/OFF with temperature setting variable

FRONT HYDRAULIC OUTRIGGER

Recommended for supreme leveling
Front spring suspension movement alleviate

PIPE RACKS

18' closed front with straps (Conventional)
Fully hydraulic lowering / raising available

BREAKOUT SYSTEM

Hydraulic breakout cylinder and hardware
(Requires auxiliary hydraulics to rear)

NIGHT LIGHTS

Derrick LED lights / guards
Cargo bay LED lights

WELL REHAB

Electronic spudder (Requires remote control response)

TAILGATE

HD drop in style

HYDRAULIC WIRE WINDERS

Automatically roll up submersible wire (Multiple models)

SEALED ROLLER BEARING SHEAVES

ILO brass bushings

HYDRAULIC WELDER

Welder/generator combo or generator only

POLY-PIPE SPOOL

53" / hydraulic / top-of-boom mounted
(Requires auxiliary hydraulics to rear)

HIGH IDLE PARAMETER SETTING

Needed with all computer-controlled engines

LONG OUTRIGGER JACKS

Recommended for all current truck models

CUSTOM-BUILT TALLER RIG FRAME

Needed for trucks with taller cabs

HEATED HYDRAULIC OIL RESERVOIR

Recommended when operating in extremely cold weather

* Load tested & certified